



GENERAL PRODUCT INFORMATION

For specific installation instructions please visit www.focalpointproducts.com

Please note: Some Focal Point window and entry features may require flashing to prevent water seepage. (See Window/Door install instructions for more details)

Storage and Handling

- Store polyurethane millwork on a flat, level surface away from extreme heat
- If the millwork is exposed to extreme heat, it should be acclimated to the installation area's temperature for 10 to 24 hours
- Repair dents or gashes with wood filler or automotive putty (recommended). Rejoin broken pieces with PL Premium Polyurethane Construction Adhesive (or equivalent)

Fastening Guidelines

- Control inevitable expansion and contraction with noncorrosive finish nails or screws and by applying PL Premium Polyurethane Construction Adhesive at each connection point and joint
- A power nail gun, adjusted to avoid over-driving the fasteners into the material, works well with Focal Point products (not to exceed 95 PSI)

Finishing

- For best results, paint Focal Point products with a good quality exterior latex paint. Focal Point products are factory primed so one coat of finish paint is typically sufficient
- Focal Point products can also be stained using a "gel" stain or can be faux finished
- See the Focal Point catalog for prefinished product options
- Remove dirt, grime or other foreign substances from the product surface prior to painting

Product Application

- Focal Point products are designed to be used for decorative purposes only unless otherwise noted. (Railing Systems, Columns, etc., do have structural integrity)
- Focal Point products can withstand temperatures up to approximately 140 degrees Fahrenheit. Avoid installation in areas that are subject to solar temperature buildup
- Focal Point products will withstand exterior elements if properly finished. Unpainted surfaces will be yellowish in color, and should be patched with putty, covered with caulk or painted during installation